

CUSTOMER NAME	DATE	CONTACT NAME	PHONE #
VALVE INFORMATION			
VALVE SIZE			
VALVE TYPE		IF BALL VALVE : 2 OR 3 PIECE	STD OR FULL PORT
BODY MATERIAL			
MEDIA		MEDIA PRESS:	MEDIA TEMP:
TYPE CONNECTION	THREADED	SOC WELD	150# FLANGE 300# FLANGE 600# FLANGE
ACTUATOR INFORMATION			
PNEUMATIC OR ELECTRIC			
PNEUMATIC INFORMATION			
AVAILABLE AIR PRESSURE			
AIR / AIR (DBLE ACTING)			
AIR / SPRING		FAIL CLOSED	FAIL OPEN
DIRECT MOUNT SOLENOID		VOLTAGE	
LIMIT SWITCH		2SPDT	2DPDT
POSITIONER		4-20 MA SIGNAL	3-15 PSI SIGNAL
SPEED CONTROL			
MUFFLER ON EXHAUST PORT			
ELECTRIC ACTUATOR INFO.			
VOLTAGE			
EXTRA LIMIT SWITCHES			
HEATER THERMOSTAT			
TROPICAL HEATER			
4-20MA POSITIONER			
NEMA4/4X/7/9 COVER			
STORED ENERGY FAIL SAFE			